Akustik +Sylomer® WF Vibration Isolators

Compact Sylomer® vibration isolation mount for lightweight equipment, designed to work in tension, compression, and shear, with a fail-safe design.

The **Akustik + Sylomer® WF** vibration isolators are designed for the **resilient isolation of lightweight equipment**, reducing the transmission of vibration and **structure-borne noise** into the building structure.

The **Sylomer® resilient element** allows the mount to work in **tension, compression, and shear**, providing considerable flexibility for different installation configurations. It is particularly suitable for the suspension or mounting of **speakers, electrical panels, HVAC equipment, fans, piping, and lightweight ductwork**.

Its metal structure incorporates a **fail-safe design** that limits excessive movement of the equipment and provides additional mechanical safety. Its **compact design** makes it particularly suitable for installations where available space is limited.

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalog without prior notice.
Document generated on 07/11/2026.

Drawings

Akustik + Sylomer WF 5 / Akustik + Sylomer WF 10 / Akustik + Sylomer WF 15





Contact the technical department to select the suitable mount for your case.

Type	Max. Load(lbs)	Code	M	Weight(lbs)
Akustik + Sylomer WF 5	2.5-5	23805	M6	0.26
		23806	M8	0.26
Akustik + Sylomer WF 10	5-10	23807	M6	0.27
		23808	M8	0.27
Akustik + Sylomer WF 15	10-15	23809	M6	0.28
		23810	M8	0.28

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalog without prior notice.
Document generated on 07/11/2026.

Elastic properties





AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalog without prior notice.
Document generated on 07/11/2026.

Technical characteristics

Contact the technical department to select the suitable mount for your case.

Advantages

Easy installation

This mount requires no major modifications to the structure for installation.

Incorporates Sylomer® elastomer, highly effective for isolating both high and low frequencies

Sylomer® provides high isolation across a wide frequency range and is particularly effective at high frequencies, effectively eliminating the transmission of structure-borne noise.

Mount offering high stability

Suspensions built with this mount barely move, thanks to a geometry designed to control the movement of the suspended element.

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalog without prior notice.
Document generated on 07/11/2026.