Tabiabsorber Acoustic Mat

Recycled rubber acoustic mat for decoupling partition walls. An effective, economical, and durable solution for reducing vibration and structure-borne noise transmission.



The TABIABSORBER is a resilient acoustic mat specifically designed to decouple partition walls from the building structure, reducing the transmission of vibration and structure-borne noise.

Manufactured from agglomerated recycled rubber particles, TABIABSORBER provides a simple, robust, and durable solution for improving the acoustic performance of partition wall assemblies.

It is available in two versions to accommodate different loads and installation requirements.

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain

Tel.: +34 843 74 00 13

sales@amcsa.es

www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalog without prior notice.
Document generated on 16/11/2026.

Drawings

Tabiabsorber 5

Type	Density(kg/m³)	Weight /m2 (lbs)	Force at traction (N/mm2)	Lengt hening till rupture (%)	Strain under pressure (N/mm2)	Temperature (Cº)	Fire resistance	Thickness(in)	Code
Tabiabsorber 5	810	9	0.04	90	0.6 a 30%	-40 a 115	Klasse B2	5 mm	30105

Tabiabsorber 5 Roll

Type	Density(kg/m³)	Weight /m2 (lbs)	Force at traction (N/mm2)	Lengt hening till rupture (%)	Strain under pressure (N/mm2)	Temperature (Cº)	Fire resistance	Thickness(in)	Code
Tabiabsorber 5 Roll	750 - 850	3.75 - 4.35	0.5 - 1.0	50 - 80	0.6 a 30%	-30 a 80	Klasse B2	5 mm	30108

Tabiabsorber 10

Type	Density(kg/m³)	Weight /m2 (lbs)	Force at traction (N/mm2)	Lengt hening till rupture (%)	Strain under pressure (N/mm2)	Temperature (Cº)	Fire resistance	Thickness(in)	Code
Tabiabsorber 10	810	18	0.06	108	0.8 a 30%	-40 a 115	Klasse B2	10 mm	30110


Tabiabsorber 8/4

Type	Density(kg/m³)	Weight /m2 (lbs)	Force at traction (N/mm2)	Lengt hening till rupture (%)	Strain under pressure (N/mm2)	Temperature (Cº)	Fire resistance	Thickness(in)	Code
Tabiabsorber 8/4	750	10	0.02	50	0.04	-30 / +80	Klasse B2	8/4	30106

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalog without prior notice.
Document generated on 16/11/2026.

Elastic properties



AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalog without prior notice.
Document generated on 16/11/2026.

Technical characteristics

- **TABIABSORBER 5**: damper shocks and insulation against noise
- **TABIABSORBER 10**: vibration isolation
- EASY INSTALLATION: Thanks to its water resistance and its rough surface, adhesion to plaster, glue and concrete is perfectly feasible.

Plates 1 X 1.25 meters. With possible supply cut by bands as needed.

Formats

- Sheets: 1x1,25m
- Tabiasorber 5 in rolls: 1x16m
- Tabiabsorber 8/4 in rolls: 1.25x8m

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalog without prior notice.
Document generated on 16/11/2026.