2 AMC Spring Isolator

Two-spring isolator for static installations, designed for machinery vibration isolation, with natural frequencies from 3.5 to 8 Hz and a rubber or Sylomer® base.

The **AMC-MECANOCAUCHO® 2 AMC Spring Isolator** is designed for the **vibration isolation of machinery and equipment incorporating rotating or reciprocating components**, which may generate dynamic forces and vibration during operation.

Its **two steel spring configuration** provides a **higher load capacity** while maintaining the high elasticity required for effective vibration isolation.

The high elasticity of the springs enables **natural frequencies from 3.5 to 8 Hz**, effectively reducing the transmission of low-frequency vibration and dynamic forces to the supporting structure.

Reducing vibration transmission helps **protect the machine and its components against dynamic stresses and fatigue**, while limiting the propagation of vibration and **structure-borne noise** to adjacent structures.

Depending on the configuration, the spring isolator can incorporate a **rubber or Sylomer® base**, improving decoupling from the supporting structure and further reducing the transmission of frequencies that may propagate through the steel springs.

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalog without prior notice.
Document generated on 07/11/2026.

Drawings

2 AMC + Sylomer®



Type	Code	Spring color	Max. Load (lbs)	K(N/mm)	A(in)	B(in)	C(in)	D(in)	E(in)	F(in)	G(in)	H(in)	Weight(lbs)
2 AMC + Sylomer®	20471	BLUE	661	103	7.87	5.35	2.95	0.47	6.69	8.66	9.61	3.19	7
	20472	WHITE	882	132	7.87	5.35	2.95	0.47	6.69	8.66	9.61	3.19	7
	20473	BLACK	1102	166	7.87	5.35	2.95	0.47	6.69	8.66	9.61	3.19	7
	20474	CREAM	1543	227	7.87	5.35	2.95	0.47	6.69	8.66	9.61	3.19	8
	20475	LIGHT GREY	2204	536	9.84	5.35	3.94	0.55	8.27	10.63	11.73	4.17	13
	20476	GREEN	3306	813	9.84	5.35	3.94	0.55	8.27	10.63	11.73	4.17	15

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalog without prior notice.
Document generated on 07/11/2026.

2 AMC



Type	Code	Spring color	Max. Load (lbs)	K(N/mm)	A(in)	B(in)	C(in)	D(in)	E(in)	F(in)	G(in)	H(in)	Weight(lbs)
2 AMC	20401	BLUE	661	103	7.87	4.88	2.95	0.47	6.69	-	-	-	7
	20411	WHITE	882	132	7.87	4.88	2.95	0.47	6.69	-	-	-	7
	20421	BLACK	1102	166	7.87	4.88	2.95	0.47	6.69	-	-	-	7
	20431	CREAM	1543	227	7.87	4.88	2.95	0.47	6.69	-	-	-	8
	20441	LIGHT GREY	2204	536	9.84	4.88	3.94	0.55	8.27	-	-	-	13
	20451	GREEN	3306	813	9.84	4.88	3.94	0.55	8.27	-	-	-	15

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalog without prior notice.
Document generated on 07/11/2026.

Elastic properties



AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalog without prior notice.
Document generated on 07/11/2026.

Advantages

Easy installation

This mount requires no major modifications to the structure for installation.

Improved isolation

It offers improved isolation compared to conventional anti-vibration mounts of similar geometry.

Excellent value

This mount delivers very high performance for its cost compared to other possible solutions.

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain

Tel.: +34 843 74 00 13

sales@amcsa.es

www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalog without prior notice.
Document generated on 07/11/2026.