Anti-rebound washer

Corrosion-resistant safety washer designed to limit rebound movement, protect the elastomer and provide mechanical retention of the equipment.



The **AMC-MECANOCAUCHO® anti-rebound washer** is designed to complement anti-vibration mounts in applications subjected to **vertical movements, shocks or high dynamic loads**.

Positioned to limit the movement of the mount under tensile loads, it acts as a **mechanical anti-rebound safety device**, controlling excessive equipment movement while maintaining the elastic operation of the anti-vibration mount.

Its **corrosion-resistant treatment** provides good protection in demanding environmental conditions and contributes to the reliability and durability of the assembly.

The **washer thickness must be selected according to the application**, the anti-vibration mount used and the allowable displacement. Please contact our technical department to determine the most suitable configuration for your application.

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain

Tel.: +34 843 74 00 13

sales@amcsa.es

www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalogue without prior notice.
Document generated on 16/11/2026.

Drawings

Cabin Mount 75 washer

Type	Code	Ø(mm)	Weight(gr)	Ø ext.(mm)	Ø int.(mm)	Thickness(mm)
Cabin Mount 75 washer	608074	16	170	76	16,5	5
	610027	20	155	76	20,5	5

Cabin Mount 80 washer

Type	Code	Ø(mm)	Weight(gr)	Ø ext.(mm)	Ø int.(mm)	Thickness(mm)
Cabin Mount 80 washer	606482	16	237	90	18	5
	606486	20	236	90	20,5	5

Cabin Mount 85 washer

Type	Code	Ø(mm)	Weight(gr)	Ø ext.(mm)	Ø int.(mm)	Thickness(mm)
Cabin Mount 85 washer	606482	16	237	90	18	5
	606486	20	236	90	20,5	5

Cabin Mount 110 washer

Type	Code	Ø(mm)	Weight(gr)	Ø ext.(mm)	Ø int.(mm)	Thickness(mm)
Cabin Mount 110 washer	611167	16	356	110	16,5	5
	606487	20	361	110	20,5	5

Cabin Mount 105 washer

Type	Code	Ø(mm)	Weight(gr)	Ø ext.(mm)	Ø int.(mm)	Thickness(mm)
Cabin Mount 105 washer	611167	16	356	110	16,5	5
	606487	20	361	110	20,5	5

Cabin Mount 130 washer

Type	Code	Ø(mm)	Weight(gr)	Ø ext.(mm)	Ø int.(mm)	Thickness(mm)
Cabin Mount 130 washer	610255	20	358	120	20,5	5

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalogue without prior notice.
Document generated on 16/11/2026.

Technical characteristics

Washers should be used, if the rubber surface is not covered with the contact surface

Advantages

Easy Installation

This mount requires minimal structural modifications, making installation quick and straightforward.

High protection against weathering and chemical contamination

The bell housing protects the rubber from ozone and UV radiation, while also preventing contact with diesel, oils or other chemicals that could damage it.

High robustness in dynamic applications for improved durability

These mounts offer enhanced robustness and are designed to withstand extreme load peaks. They are especially recommended where good durability is required in demanding applications.

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain

Tel.: +34 843 74 00 13

sales@amcsa.es

www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalogue without prior notice.
Document generated on 16/11/2026.