

CB Washer

ZnNi-coated steel washer designed to provide mechanical retention for CB Vibration Isolators, limit excessive movement and maintain the fail-safe function under high dynamic loads.



The **AMC-MECANOCAUCHO® CB Washer** is specifically designed for use with **CB Vibration Isolators**, installed in pairs on either side of the chassis or structure to be isolated.

Manufactured from **ZnNi-coated steel**, it provides **excellent corrosion resistance** and contributes to the **mechanical retention of the vibration isolator** when subjected to high loads.

Together with the through-bolt and CB Vibration Isolators, the washer forms part of the **multidirectional snubbing system**, helping to **limit excessive movement** and maintain the **fail-safe function** under shocks, accelerations and high dynamic loads.

Its robust design makes it an essential component of the CB isolation system for **mobile machinery, cabs, off-highway equipment and other applications subjected to demanding dynamic conditions**.

Drawings

CB 40 WASHER

Type	Weight(lbs)	Ø ext.(in)	Ø int.(in)	Thickness(in)	Code
CB 40 WASHER	0.04	1.5	0.33	0.08	610053

CB 60 WASHER

Type	Weight(lbs)	Ø ext.(in)	Ø int.(in)	Thickness(in)	Code
CB 60 WASHER	0.28	2.6	0.65	0.2	606130

CB 65 WASHER

Type	Weight(lbs)	Ø ext.(in)	Ø int.(in)	Thickness(in)	Code
CB 65 WASHER	0.31	2.64	0.73	0.2	706004

CB 76 WASHER

Type	Weight(lbs)	Ø ext.(in)	Ø int.(in)	Thickness(in)	Code
CB 76 WASHER	0.39	2.99	0.65	0.2	608074

CB 80 WASHER

Type	Weight(lbs)	Ø ext.(in)	Ø int.(in)	Thickness(in)	Code
CB 80 WASHER	0.39	2.99	0.65	0.2	608074

CB 110 WASHER

Type	Weight(lbs)	Ø ext.(in)	Ø int.(in)	Thickness(in)	Code
CB 110 WASHER	1	4.33	0.91	0.2	610192

CB 125 WASHER

Type	Weight(lbs)	Ø ext.(in)	Ø int.(in)	Thickness(in)	Code
CB 125 WASHER	3	5.71	0.96	0.39	608529

CB 130 WASHER

Type	Weight(lbs)	Ø ext.(in)	Ø int.(in)	Thickness(in)	Code
CB 130 WASHER	3	5.71	1.2	0.39	608278

CB 150 WASHER

Type	Weight(lbs)	Ø ext.(in)	Ø int.(in)	Thickness(in)	Code
CB 150 WASHER	3	5.71	1.2	0.39	608278

Technical characteristics

Washers should be used, if the rubber surface is not covered with the contact surface

