Akustik 1 Low + Sylomer® Acoustic Hanger

Low-profile acoustic hanger with Sylomer® for suspended ceilings. Compact design for applications with limited installation height.



The Akustik 1 Low + Sylomer® acoustic hanger is specifically designed for the vibration isolation of suspended ceilings where the available installation height is limited.

Its low-profile design minimises the space required between the supporting structure and the suspended ceiling while maintaining effective vibration isolation. The Sylomer® elastic element effectively reduces the transmission of vibration and structure-borne noise through the building structure.

It is particularly suitable for projects requiring a minimal suspension height without compromising acoustic performance.

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalogue without prior notice.
Document generated on 07/11/2026.

Drawings

Akustik 1 Low + Sylomer®15 Type A / Akustik 1 Low + Sylomer®30 Type A / Akustik 1 Low + Sylomer®50 Type A / Akustik 1 Low + Sylomer®75 Type A



Type	Max.Load (kg)	Code	Weight(kg)
Akustik 1 Low + Sylomer®15 Type A	15	23773	0.12
Akustik 1 Low + Sylomer®30 Type A	30	23771	0.105
Akustik 1 Low + Sylomer®50 Type A	50	23774	0.125
Akustik 1 Low + Sylomer®75 Type A	75	23772	0.13

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalogue without prior notice.
Document generated on 07/11/2026.

Elastic properties

LOAD DEFLECTION GRAPHS

Akustik + Sylomer **15**



Akustik + Sylomer **30**



Akustik + Sylomer **50**



Akustik + Sylomer **75**



NATURAL FREQUENCY GRAPHS

Akustik + Sylomer **15**



Akustik + Sylomer **30**



Akustik + Sylomer **50**



Akustik + Sylomer **75**



AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalogue without prior notice.
Document generated on 07/11/2026.

Advantages

Easy Installation

This mount requires minimal structural modifications, making installation quick and straightforward.

Incorporates Sylomer® elastomer, highly effective for isolating both high and low frequencies

Sylomer® provides high isolation across a wide frequency range and is particularly effective at high frequencies, effectively eliminating the transmission of structure-borne noise.

Secure ceiling anchorage

With more than one fixing point to the overhead slab, it is particularly reliable for anchorages with low load-bearing capacity.

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain

Tel.: +34 843 74 00 13

sales@amcsa.es

www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalogue without prior notice.
Document generated on 07/11/2026.