Akustik 3 +Sylomer®

Compact acoustic hanger with Sylomer®. Direct slab fixing for suspended ceilings, HVAC ducts, pipework and mechanical services.

The AMC-MECANOCAUCHO® Akustik 3 + Sylomer® range has been developed for the vibration isolation of suspended ceilings, HVAC ducts, pipework and suspended mechanical equipment in demanding building acoustics applications.

Its integrated Sylomer® microcellular polyurethane element provides significantly higher vibration isolation than conventional rubber or cork mounts, particularly at medium and high frequencies. The range is available in two Sylomer® grades, allowing the isolator stiffness to be matched to the supported load for optimum acoustic performance.

A wide selection of brackets and fixing accessories enables quick installation in virtually any suspended application. The heavy-duty steel components withstand tensile loads from 650 kg to 1,000 kg and are protected by a corrosion-resistant finish for long-term durability in demanding environments.

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalogue without prior notice.
Document generated on 11/11/2026.

Drawings

Akustik 3 + Sylomer®15 Type A / Akustik 3 + Sylomer®30 Type A / Akustik 3 + Sylomer®50 Type A / Akustik 3 + Sylomer®75 Type A



Type	SUMMARY	Max.Load (kg)	Code	M	Weight(kg)
Akustik 3 + Sylomer®15 Type A	Metal armor of the akustik 3 secured to the ceiling by an screwand with a nut.	15	23135	M6	0.133
			23207	M8	0.133
Akustik 3 + Sylomer®30 Type A	Metal armor of the akustik 3 secured to the ceiling by an screw and with a nut.	30	23503	M6	0.13
			23274	M8	0.13
Akustik 3 + Sylomer®50 Type A	Metal armor of the akustik 3 secured to the ceiling by an screwand with a nut.	50	23569	M6	0.13
			23275	M8	0.13
Akustik 3 + Sylomer®75 Type A	Metal armor of the akustik 3 secured to the ceiling by an screw and with a nut.	75	23519	M6	0.14
			23270	M8	0.157

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalogue without prior notice.
Document generated on 11/11/2026.

Akustik 3 + Sylomer®15 Type B / Akustik 3 + Sylomer®30 Type B / Akustik 3 + Sylomer®50 Type B / Akustik 3 + Sylomer®75 Type B

15
30
50
75





Type	SUMMARY	Max.Load (kg)	Code	M	Weight(kg)
Akustik 3 + Sylomer®15 Type B	Metal armor of the akustik 3 secured to the ceiling by an screwand with a nut.	15	23186	M6	0.133
			23208	M8	0.133
Akustik 3 + Sylomer®30 Type B	Metal armor of the Akustik 3 secured to the ceiling by a welded nut.	30	23511	M6	0.136
			23881	M8	0.129
Akustik 3 + Sylomer®50 Type B	Metal armor of the Akustik 3 secured to the ceiling by a welded nut.	50	23570	M6	0.133
			23883	M8	0.137
Akustik 3 + Sylomer®75 Type B	Metal armor of the Akustik 3 secured to the ceiling by a welded nut.	75	23527	M6	0.14
			23882	M8	0.137

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalogue without prior notice.
Document generated on 11/11/2026.

Elastic properties

LOAD DEFLECTION GRAPHS

Akustik + Sylomer **15**



Akustik + Sylomer **30**



Akustik + Sylomer **50**



Akustik + Sylomer **75**



NATURAL FREQUENCY GRAPHS

Akustik + Sylomer **15**



Akustik + Sylomer **30**



Akustik + Sylomer **50**



Akustik + Sylomer **75**



AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalogue without prior notice.
Document generated on 11/11/2026.

Advantages

Easy Installation

This mount requires minimal structural modifications, making installation quick and straightforward.

Incorporates Sylomer® elastomer, highly effective for isolating both high and low frequencies

Sylomer® provides high isolation across a wide frequency range and is particularly effective at high frequencies, effectively eliminating the transmission of structure-borne noise.

Improved isolation

It offers improved isolation compared with conventional anti-vibration mounts of similar geometry.

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain

Tel.: +34 843 74 00 13

sales@amcsa.es

www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalogue without prior notice.