

Ceiling mounts VT NT

Spring hangers with a through-hole upper bracket, designed for low-frequency vibration and structure-borne noise isolation.




The **AMC-MECANOCAUCHO® VT NT Spring Hangers** are designed for the resilient suspension of **acoustic ceilings and suspended equipment** requiring a high level of vibration isolation.

They incorporate **Vibrabsorber springs** specifically designed to provide effective isolation of low-frequency vibrations. A rubber bushing at the upper connection prevents direct metal-to-metal contact and helps maintain acoustic isolation when the suspension rod is not perfectly aligned.

The robust metal housing provides reliable mechanical support, while the **zinc-plated finish provides corrosion protection** for long-term service.

Drawings

VT NT 8 / VT NT 15 / VT NT 25 / VT NT 50 / VT NT 75 / VT NT 100 / VT NT 125 / VT NT 150R /
VT NT 150 / VT NT 200 / VT NT 250 / VT NT 350 / VT NT 500 / VT NT 750



Type	Max. Permanent Load (lbs)	Spring color	A(in)	C(in)	E(in)	H(in)	Code	B(in)	Weight(lbs)
VT NT 8	18	BLACK	3.15	0.47	1.97	4.72	20248	0.41	1
VT NT 15	33	BLACK	3.15	0.47	1.97	4.72	20273	0.41	1
VT NT 25	55	BLACK	3.15	0.47	1.97	4.72	20261	0.41	2
VT NT 50	110	BLUE	3.15	0.47	1.97	4.72	20262	0.41	2
VT NT 75	165	GREY	3.15	0.47	1.97	4.72	20263	0.41	2
VT NT 100	220	BEIGE	3.15	0.47	1.97	4.72	20264	0.41	2
VT NT 125	276	WHITE	3.15	0.47	1.97	4.72	20265	0.41	2
VT NT 150R	331	BLACK	3.15	0.47	1.97	4.72	20275	0.41	2
VT NT 150	331	BLUE	4.72	0.63	3.15	6.3	20266	0.64	5
VT NT 200	441	WHITE	4.72	0.63	3.15	6.3	20268	0.64	5
VT NT 250	551	BLACK	4.72	0.63	3.15	6.3	20269	0.64	5
VT NT 350	771	CREAM	4.72	0.63	3.15	6.3	20270	0.64	5
VT NT 500	1102	LIGHT GREY	5.51	0.63	3.94	7.09	20267	0.66	10
VT NT 750	1653	GREEN	5.51	0.63	3.94	7.09	20271	0.66	12



AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain



Tel.: +34 843 74 00 13



sales@amcsa.es





www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalog without prior notice.

Document generated on 05/10/2026.

Elastic properties



AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain



Tel.: +34 843 74 00 13



sales@amcsa.es



www.mecanocaucho.com

Technical characteristics

NEVER METAL TO METAL CONTACT

The hanger has a clearance that allows the threaded rod to swing within a 35° angle envelope to absorb irregularities in the ceiling.



AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain



Tel.: +34 843 74 00 13



sales@amcsa.es



www.mecanocaucho.com