

Type C Diabolo wasted Bobbins

Diabolo wasted shape anti-vibration bobbins with female threads on both sides, offering high elasticity and low stiffness for enhanced vibration isolation.



The **AMC-MECANOCAUCHO® Type C Diabolo Bobbins** are rubber-metal anti-vibration elements designed to provide **greater elasticity than conventional cylindrical bobbins**, allowing higher levels of vibration isolation.


Their **diabolo-shaped geometry** allows greater elastomer deformation and provides **lower stiffness**. This results in **lower natural frequencies**, making them particularly suitable for applications where a high degree of vibration isolation is required.

They consist of an **elastomer body vulcanised between two parallel metal parts**, each incorporating a **female thread**. This configuration allows bolted fixing from both sides and facilitates installation where external threaded studs are not required.

Thanks to their high elasticity, Type C Diabolo Bobbins are particularly suitable for **light equipment, fans, pumps, small engines, instruments and industrial machinery** requiring effective vibration isolation.

Drawings

F.00N / F.3 / F.0N / F.9 / F.7 / F.1 / F.2 / F.4 / F.8 / F.5 / F.6



Type	A(mm)	B(mm)	D(mm)	COMPRESSION Max. Load (daN)	COMPRESSION Deflection (mm)	SHEAR Max. Load (daN)	SHEAR Deflection (mm)	Code	C(mm)	Weight(kg)
F.00N	20	19	13,5	12	2,5	3	5	129202	M-6	0.01
F.3	30	25	24	40	5	4	4,5	129203	M-8	0.055
F.0N	40	28	19	30	5	2,5	4,5	129204	M-10	0.074
								129213	M-8	0.058
F.9	40	30	26	45	3	4	4,5	129205	M-8	0.069
F.7	44	42	25	50	6	9	6	129206	M-8	0.093
F.1	60	44	24	40	5	7	5	129207	M-8	0.164
F.2	60	44	34	75	5	12	6	129208	M-8	0.202
								128002	M-10	0.198
F.4	60	60	50	150	8	30	10	129209	M-10	0.282
F.8	60	36	37	100	3,5	20	8	129210	M-10	0.187
F.5	80	70	70	300	9,5	55	9,8	129211	M-14	0.554
F.6	95	76	80	400	9,5	70	8	129212	M-16	0.834

Technical characteristics

Depending on the size of the rubber block, the AMC Mecanocaucho® bobbing has more or less elasticity, which is greater particularly in all directions perpendicular to its axis (shear). The AMC Mecanocaucho® bobbing thus makes it possible to make joints which permit major relative movements, up to several millimetres (in the case of heat expansion, chassis deformations, etc.). The AMC Mecanocaucho® bobbing serves very well for the vibration isolation of machines where the vibrations are perpendicular to their axis, unless these stresses are too much when applied in this direction.