EP 650

Resilient mount for double independent wall linings with lateral fixing. Designed for acoustic decoupling at junctions with perpendicular walls.

The **EP 650** is a resilient mount designed to provide an **acoustically decoupled connection for double independent wall linings** at lateral junctions and connections with perpendicular walls.

Its specific geometry incorporates a **metal bracket with a 90° return**, allowing lateral fixing to the adjacent wall. The different parts of the mount are connected by **resilient rubber elements**, providing mechanical stability without creating a rigid connection between the structures.

This design helps limit the formation of **acoustic bridges at wall junctions** and reduces the transmission of vibrations and **structure-borne sound** between adjacent walls.

The EP 650 is particularly suitable for **double independent wall linings, studios, rehearsal rooms, technical rooms and soundproofing projects** incorporating changes in direction or more complex wall configurations.

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalogue without prior notice.
Document generated on 11/11/2026.

Drawings

E.P. 650



Type	SUMMARY	Max. Load(kg)	Code	Weight(kg)
E.P. 650	This damper is conceived to be fixed between two elements through two metal parts with “pre-drilled holes”. The metal parts are easy to cut in order to adapt better to each work. Following this idea we can realise a great amount of variants in order to adapt better to each work. Please enquire us if you need a more adapted system for your work.	-	24009	0,185

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalogue without prior notice.
Document generated on 11/11/2026.

Technical characteristics

- Similar to the EP 600 but with an **additional bend for side mounting**
- Ideal for fixing to **walls perpendicular to the channel**
- **Zinc-plated metal plates** and elastic rubber core
- Effective decoupling between structures
- Suitable for **double wall linings and structural junctions**
- Improved acoustic isolation in complex configurations

Advantages

Easy Installation

This mount requires minimal structural modifications, making installation quick and straightforward.

Excellent value for money

This mount delivers very high performance for its cost compared with other possible solutions.

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain

Tel.: +34 843 74 00 13

sales@amcsa.es

www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalogue without prior notice.
Document generated on 11/11/2026.