FAI

Fire-resistant panel with Type F polyurethane foam and aluminised glass fibre facing. Ideal for acoustic isolation in demanding industrial environments.



The AKUSTIKABSORBER FAI range consists of panels manufactured from Type F fire-resistant polyurethane foam, with an aluminised glass fibre technical facing on the exposed surface. This configuration provides excellent fire performance together with high mechanical, thermal and chemical resistance, making it an effective and durable acoustic isolation material for demanding industrial and technical environments.

The Type F foam core provides a certain degree of sound absorption, particularly at medium and high frequencies, whilst the aluminised glass fibre facing acts as a protective barrier against aggressive agents such as oils, splashes and radiant heat. Although sound absorption is not its primary function, FAI provides an effective combination of protection and acoustic isolation, making it particularly suitable for applications requiring both fire safety and durability.

Thanks to its robust construction and technical finish, FAI is commonly used in acoustic enclosures, electrical cabinets, machinery rooms, technical enclosures and ventilation ducts where a protected surface exposed to the environment and an effective acoustic barrier are required.

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalogue without prior notice.
Document generated on 15/11/2026.

Drawings

FAI-15 sheet

Type	Code	Self-adhesive	Rw(dB)	Weight/m2 (kg)
FAI-15 sheet	26251	-	19	1,335

FAI-15 A sheet

Type	Code	Self-adhesive	Rw(dB)	Weight/m2 (kg)
FAI-15 A sheet	26253	✓	19	1,335

FAI-25 sheet

Type	Code	Self-adhesive	Rw(dB)	Weight/m2 (kg)
FAI-25 sheet	26252	-	23	2,085


FAI-25 A sheet


Type	Code	Self-adhesive	Rw(dB)	Weight/m2 (kg)
FAI-25 A sheet	26254	✓	23	2,085

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalogue without prior notice.
Document generated on 15/11/2026.

Elastic properties





AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalogue without prior notice.
Document generated on 15/11/2026.

Technical characteristics

- CompositionAluminium facing with fibreglass support and M-1 class fireresistant absorbing polyurethane foam.
- Thicknesses15mm 25mm

Formats

- Sheets1200x1000 mm
15mm thick, 8 Sheets per box.
25mm thick, 5 Sheets per box.

Advantages

Material highly resistant to abrasion and heavily soiled environments

Highly abrasion-resistant material, suitable for frequent cleaning.

Excellent fire-retardant performance

This material has good fire-retardant properties and is suitable for industrial applications with a fire risk.

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalogue without prior notice.
Document generated on 15/11/2026.