

FAIM

Fire-resistant multilayer acoustic panel with Type F foam, rear heavy mass layer and aluminised technical facing. High-performance acoustic isolation, absorption and durability for industrial environments.



The AKUSTIKABSORBER FAIM range is designed to provide a complete acoustic isolation and absorption system for demanding environments. It combines Type F fire-resistant foam, an aluminised glass fibre technical facing on the exposed surface and a heavy mass layer bonded to the rear. This multilayer construction provides an excellent combination of airborne noise isolation, fire resistance and acoustic absorption at medium and high frequencies.

The rear acoustic mass, typically between 2 and 5 kg/m², significantly improves sound isolation, particularly at low frequencies where foam alone is less effective. The aluminised glass fibre facing also provides high resistance to abrasion, heat and chemical agents, making FAIM particularly suitable for industrial environments, technical rooms, machinery, electrical compartments and areas exposed to oils, splashes or contaminants.

FAIM is normally installed with the foam facing the noise source to provide acoustic absorption, whilst the rear heavy mass layer acts as an acoustic barrier, reducing noise transmission. The complete assembly maintains fire-resistant performance suitable for technical applications with fire-safety requirements.

Drawings

FAIM-15 sheet

Type	Code	Self-adhesive	Rw(dB)	Weight/m2 (kg)
FAIM-15 sheet	26271	-	22	7,335

FAIM-15 A sheet

Type	Code	Self-adhesive	Rw(dB)	Weight/m2 (kg)
FAIM-15 A sheet	26273	✓	22	7,335



FAIM-25 sheet

Type	Code	Self-adhesive	Rw(dB)	Weight/m2 (kg)
FAIM-25 sheet	26272	-	25	8,085

FAIM-25 A sheet

Type	Code	Self-adhesive	Rw(dB)	Weight/m2 (kg)
FAIM-25 A sheet	26274	✓	25	8,085

Elastic properties



Technical characteristics

- Composition Aluminium facing with fibreglass support, M- 1 class fire-resistant absorbing polyurethane foam and 5 Kg/m² heavy viscoelastic mass
- Thicknesses 15mm 25mm

Formats

- Sheets 1200x1000 mm
15mm thick, 8 Sheets per box.
25mm thick, 5 Sheets per box.