
FDM

Fire-resistant acoustic panel with heavy mass layer and perforated PVC facing. Combines sound absorption, airborne sound isolation, and a clean finish for cabs and technical interiors.



The **AKUSTIKABSORBER FDM** is a multilayer acoustic panel combining **sound absorption, airborne sound isolation, and a technical finish** in a compact solution. It is particularly suitable for **cab interiors, technical rooms, and applications where acoustic performance must be combined with a clean, professional appearance**.

The panel consists of **fire-resistant Type F polyurethane foam**, a **heavy mass layer bonded to the rear** to improve airborne sound isolation, and a **beige perforated PVC facing**. The foam provides effective **sound absorption at mid and high frequencies**, while the heavy mass layer increases the surface mass of the system and helps **reduce airborne sound transmission**.

The perforated PVC facing protects the foam while allowing sound waves to reach the absorptive core. Its beige finish also provides a **clean and professional appearance**, making it particularly suitable for visible interior applications.

Thanks to this multilayer construction, FDM is particularly suitable for **machinery cabs, industrial vehicles, control rooms, acoustic enclosures, and interior panels** where a balance of **sound absorption, sound isolation, fire performance, and appearance** is required.

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalog without prior notice.
Document generated on 15/11/2026.

Drawings

FDM-15 sheet

Type	Code	Self-adhesive	Rw(dB)	Weight /m2 (lbs)
FDM-15 sheet	26281	-	15	16

FDM-15 A sheet

Type	Code	Self-adhesive	Rw(dB)	Weight /m2 (lbs)
FDM-15 A sheet	26283	✓	15	16

FDM-25 sheet

Type	Code	Self-adhesive	Rw(dB)	Weight /m2 (lbs)
FDM-25 sheet	26282	-	13	18


FDM-25 A sheet


Type	Code	Self-adhesive	Rw(dB)	Weight /m2 (lbs)
FDM-25 A sheet	26284	✓	13	18

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalog without prior notice.
Document generated on 15/11/2026.

Elastic properties





AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalog without prior notice.
Document generated on 15/11/2026.

Technical characteristics

- CompositionBeige colour perforated PVC facing, M-1 class fireresistant absorbing polyurethane foam and 5 Kg/m2 heavy viscoelastic mass.
- Thicknesses15mm 25mm

Formats

- Sheets1200x1000 mm
15mm thick, 8 Sheets per box.
25mm thick, 5 Sheets per box.

Advantages

High absorption capacity

This material is highly porous and, thanks to its high absorption capacity, reduces reflections and reverberation time in enclosed spaces.

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalog without prior notice.
Document generated on 15/11/2026.