
FIM

Fire-resistant acoustic panel with durable fiberglass facing and rear heavy mass layer. Multilayer solution for high-performance and robust sound isolation.



The **AKUSTIKABSORBER FIM** is a multilayer acoustic panel designed to provide **high airborne sound isolation**, combining sound absorption, mass, and mechanical durability in a single technical product. It consists of **fire-resistant Type F polyurethane foam**, a **durable fiberglass facing**, and a **heavy mass layer bonded to the rear**, which acts as an acoustic barrier when positioned against the supporting surface during installation.

The Type F foam provides effective **sound absorption**, particularly at mid and high frequencies. The external fiberglass facing mechanically reinforces the panel and protects the foam against **wear, abrasion, and demanding operating conditions**. The rear heavy mass layer increases the surface mass of the system, helping to **reduce airborne sound transmission**.

This multilayer construction makes FIM particularly suitable for **demanding industrial applications, acoustic enclosures, technical rooms, machinery housings, and cabs** where high sound isolation, effective absorption, and **high surface resistance** are required.

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalog without prior notice.
Document generated on 15/11/2026.

Drawings

FIM-15 sheet

Type	Code	Self-adhesive	Rw(dB)	Weight /m2 (lbs)
FIM-15 sheet	26221	-	24	16

FIM-15 A sheet

Type	Code	Self-adhesive	Rw(dB)	Weight /m2 (lbs)
FIM-15 A sheet	26211	✓	24	16

FIM-25 sheet


Type	Code	Self-adhesive	Rw(dB)	Weight /m2 (lbs)
FIM-25 sheet	26225	-	24	18


FIM-25 A sheet

Type	Code	Self-adhesive	Rw(dB)	Weight /m2 (lbs)
FIM-25 A sheet	26215	✓	24	18

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalog without prior notice.
Document generated on 15/11/2026.

Elastic properties





AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalog without prior notice.
Document generated on 15/11/2026.

Technical characteristics

• CompositionFiberglass facing, M- 1 class fire-resistant absorbing polyurethane foam and 5 Kg/m2 heavy viscoelastic mass.

• Thicknesses15mm 25mm

Formats

• Sheets1200x1000 mm
15mm thick, 8 Sheets per box.
25mm thick, 5 Sheets per box.

Advantages

Material highly resistant to abrasion and dirty environments

Highly abrasion-resistant material, suitable for frequent cleaning.

High absorption capacity

This material is highly porous and, thanks to its high absorption capacity, reduces reflections and reverberation time in enclosed spaces.

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalog without prior notice.
Document generated on 15/11/2026.