

BF Vibration Isolators for Floating Floors

Cylindrical rubber vibration isolators for floating floors. Available in different diameters and heights to match isolation performance to project loads.



The BF vibration isolators are designed for floating floor systems requiring effective isolation of vibration and structure-borne noise.



Installed beneath the floating floor, they provide elastic decoupling from the supporting structure, reducing the transmission of vibration into the building.

They are manufactured from rubber with excellent mechanical and elastic properties and are available in different diameters and heights, allowing load capacity and isolation performance to be matched to the requirements of each project.

They can also be used for vibration isolation of machinery operating at speeds of 700 rpm and above, provided that the load and frequency characteristics of the installation are suitable.




Drawings

BF 50 / BF 125 / BF 200 / BF 400 / BF 500



Type	Max. Permanent Load (lbs)	Height(in)	Ø(in)	Code	Weight(lbs)
BF 50	110	1.1	1.57	24201	0.09
BF 125	276	1.42	2.36	24202	0.26
BF 200	441	1.57	3.15	24203	1
BF 400	882	1.57	3.74	24204	1
BF 500	1102	1.97	3.15	24218	1

Elastic properties



AMC MECANOCAUCHO

Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain



Tel.: +34 843 74 00 13
Fax: +34 943 69 62 19



sales@amcsa.es



www.mecanocaucho.com
www.akustik.com