MD Vibration Isolators

High-damping vibration isolators designed to combine vibration isolation, stability and motion control.

The **AMC-MECANOCAUCHO® MD vibration isolators** have a similar design to the BSB and BRB ranges. Their main distinguishing feature is the use of a **high internal damping synthetic elastomer compound**.

This formulation helps **dissipate vibrational energy and reduce motion amplitudes**, particularly during **transient conditions and when passing through resonance frequencies**. MD vibration isolators therefore provide an excellent balance of **vibration isolation, damping and equipment stability**.

Thanks to their ability to control oscillations, they are particularly well suited for **engines, generator sets, pumps, compressors, and mobile or stationary machinery** subjected to dynamic loads and requiring a **stable, highly damped suspension**.

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalog without prior notice.
Document generated on 07/11/2026.

Drawings

A / B / C / D



Type	Tightening torque Max. (Nm)	Max. Load(lbs)	Weight(lbs)	Code
A	2.17	287	1	135210
B	2.17	231	1	135212
C	2.17	154	1	135213
D	2.17	110	1	135219

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalog without prior notice.
Document generated on 07/11/2026.

Elastic properties





AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalog without prior notice.
Document generated on 07/11/2026.

Technical characteristics

• The top metal cap protects the rubber section from possible deisel , oil splashes.

• It has an electrolytic coating that protects the metal parts against corrosion.

• The mounts have an interlocking metal component that provides fail-safe protection for mobile applications. This device limits vertical movement when the mounts are subjected to shock loads in transit .

Advantages

Easy installation

This mount requires no major modifications to the structure for installation.

Mount offering high stability

Suspensions built with this mount barely move, thanks to a geometry designed to control the movement of the suspended element.

Superior damping that reduces amplification and controls movement

The superior damping enhances equipment stability: when passing through resonance during startup and shutdown, energy is absorbed, resulting in reduced amplitude.

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalog without prior notice.
Document generated on 07/11/2026.