

PAI

Fire-resistant acoustic isolation panel with polyurethane foam and aluminized fiberglass facing, designed to reduce noise transmission in demanding industrial environments.



The AKUSTIKABSORBER PAI range consists of multilayer acoustic panels developed for applications where sound isolation must be combined with high fire resistance and surface abrasion resistance. These panels combine flexible polyurethane foam with a technical facing consisting of an aluminized fiberglass layer, which acts as a protective barrier and structural reinforcement. This facing provides the assembly with excellent fire performance, allowing its use in demanding industrial environments subject to specific safety requirements.

The PAI design is optimized to reduce airborne noise transmission, making use of the surface mass of the facing and the decoupling properties of the foam. Although its sound absorption performance is not particularly significant — as the foam is closed by the outer film — its primary function is to act as an acoustic isolation barrier, limiting sound propagation through increased mass and the acoustic discontinuity between layers.

It is an ideal option for machinery enclosures, technical partitions, acoustic compartments, and interior linings exposed to heat, sparks, or abrasive particles, or wherever a resistant and safe material is required. The facing also facilitates cleaning and prevents the accumulation of dust and contaminants.



AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain

Tel.: +34 843 74 00 13

sales@amcsa.es

www.mecanocaucho.com

Drawings

PAI-15 sheet

Type	Code	Self-adhesive	Rw(dB)	Weight /m2 (lbs)
PAI-15 sheet	26025	-	17	2

PAI-15 A sheet

Type	Code	Self-adhesive	Rw(dB)	Weight /m2 (lbs)
PAI-15 A sheet	26170	✓	17	2

PAI-15 roll

Type	Code	Self-adhesive	Rw(dB)	Weight /m2 (lbs)
PAI-15 roll	26022	-	17	2

PAI-15 A roll

Type	Code	Self-adhesive	Rw(dB)	Weight /m2 (lbs)
PAI-15 A roll	26172	✓	17	2

PAI-25 sheet

Type	Code	Self-adhesive	Rw(dB)	Weight /m2 (lbs)
PAI-25 sheet	26026	-	19	3

PAI-25 A sheet

Type	Code	Self-adhesive	Rw(dB)	Weight /m2 (lbs)
PAI-25 A sheet	26127	✓	19	3

PAI-25 roll

Type	Code	Self-adhesive	Rw(dB)	Weight /m2 (lbs)
PAI-25 roll	26023	-	19	3

PAI-25 A roll

Type	Code	Self-adhesive	Rw(dB)	Weight /m2 (lbs)
PAI-25 A roll	26173	✓	19	3

PAI-40 sheet

Type	Code	Self-adhesive	Rw(dB)	Weight /m2 (lbs)
PAI-40 sheet	26027	-	19	4

PAI-40 A sheet

Type	Code	Self-adhesive	Rw(dB)	Weight /m2 (lbs)
PAI-40 A sheet	26171	✓	19	4



PAI-40 roll

Type	Code	Self-adhesive	Rw(dB)	Weight /m2 (lbs)
PAI-40 roll	26024	-	19	4

PAI-40 A roll

Type	Code	Self-adhesive	Rw(dB)	Weight /m2 (lbs)
PAI-40 A roll	26174	✓	19	4

Elastic properties



Technical characteristics

- Composition Aluminium facing with fibreglass support and absorbing polyurethane foam.
- Thicknesses 15mm 25mm 40mm

Formats

- Sheets 1200x1000 mm
15mm thick, 8 Sheets per box.
25mm thick, 5 Sheets per box.
40mm thick, 3 Sheets per box.
- Rolls 1500mm wide x approx. 20m long



AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain



Tel.: +34 843 74 00 13



sales@amcsa.es



www.mecanocaucho.com