
PDM

Polyurethane foam acoustic panel with heavy mass layer and perforated PVC facing. Cost-effective solution combining sound absorption and isolation for applications without specific fire performance requirements.



The **AKUSTIKABSORBER PDM** is a multilayer acoustic panel designed to provide an effective combination of **sound absorption and airborne sound isolation** in applications where no specific fire performance is required. It consists of **flexible polyurethane foam**, a **heavy mass layer bonded to the rear**, and a **perforated PVC facing** providing both surface protection and a technical finish.

The polyurethane foam provides effective **sound absorption at mid and high frequencies**. The rear heavy mass layer increases the surface mass of the system, helping to **reduce airborne sound transmission**. The perforated PVC facing allows sound to reach the absorptive foam while protecting its surface and providing a **clean, professional finish**.

Thanks to this multilayer construction, PDM provides a **cost-effective and efficient solution** for **machinery enclosures, cabs, interior panels, acoustic cabinets, and technical enclosures** where improved sound isolation and absorption are required without specific fire performance requirements.

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalog without prior notice.
Document generated on 16/11/2026.

Drawings

PDM-15 sheet

Type	Code	Self-adhesive	Rw(dB)	Weight /m2 (lbs)
PDM-15 sheet	26108	-	12	16

PDM-15 A sheet

Type	Code	Self-adhesive	Rw(dB)	Weight /m2 (lbs)
PDM-15 A sheet	26102	✓	12	16

PDM-25 sheet

Type	Code	Self-adhesive	Rw(dB)	Weight /m2 (lbs)
PDM-25 sheet	26110	-	12	16

PDM-25 A sheet

Type	Code	Self-adhesive	Rw(dB)	Weight /m2 (lbs)
PDM-25 A sheet	26104	✓	12	16

PDM-40 sheet

Type	Code	Self-adhesive	Rw(dB)	Weight /m2 (lbs)
PDM-40 sheet	26112	-	20	17


PDM-40 A sheet


Type	Code	Self-adhesive	Rw(dB)	Weight /m2 (lbs)
PDM-40 A sheet	26106	✓	20	17

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalog without prior notice.
Document generated on 16/11/2026.

Elastic properties





AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalog without prior notice.
Document generated on 16/11/2026.

Technical characteristics

- CompositionBeige colour perforated PVC facing, absorbing polyurethane foam and 5 Kg/m2 heavy viscoelastic mass.
- Thicknesses15mm 25mm 40mm

Formats

- Sheets1200x1000 mm

15mm thick, 8 Sheets per box.
25mm thick, 5 Sheets per box.
40mm thick, 3 Sheets per box.

Advantages

High absorption capacity

This material is highly porous and, thanks to its high absorption capacity, reduces reflections and reverberation time in enclosed spaces.

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalog without prior notice.
Document generated on 16/11/2026.