SFC

High-capacity marine exhaust mount for loads from 2,700 to 3,400 kg, with fail-safe mechanical restraint and integrated thermal insulation.

The **SFC AMC-MECANOCAUCHO® marine exhaust mounts** are designed to provide **elastic support for heavy exhaust systems**, with load capacities ranging from **2,700 to 3,400 kg**.

Their robust design accommodates **high static and dynamic loads** whilst reducing the transmission of **vibration and structure-borne noise** to the vessel structure. An integrated **fail-safe device** provides mechanical restraint against tensile loads and the dynamic forces encountered in marine service.

SFC mounts also incorporate a **thermal insulation plate** designed to limit heat transfer between the exhaust pipe and the mount. Their design accommodates movements associated with **thermal expansion and contraction** of the exhaust system.

Thanks to their **high load capacity, mechanical safety and corrosion resistance**, SFC mounts are particularly suitable for **exhaust systems of high-power marine engines and generator sets**.

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalogue without prior notice.
Document generated on 07/11/2026.

Drawings

TYPE A / TYPE B

TYPE A



TYPE B



Type	Code	Descrip.	Max. Load (kg)	A(mm)	Shore	B(mm)	C(mm)	D(mm)	E(mm)	F(mm)	G(mm)	H(mm)	M
TYPE A	709301	SFC-80	270	12	60 Sh	34	123,2	10	92	150	50	4,4	M12
	709305	SFC-110	420	12	60 Sh	41	143	13	106	175	50	6	M12
	709311	SFC-150	800	12	60 Sh	53,5	182	14,5	156	218	90	6	M16
TYPE B	709312	SFC-180	1700	12	60 Sh	55	150	14	186	181	90	-	M20
	709315	SFC-220	3400	12	60 Sh	105	180	19	230	220	90	-	M24

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalogue without prior notice.
Document generated on 07/11/2026.

Elastic properties





AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalogue without prior notice.
Document generated on 07/11/2026.

Technical characteristics

Their particular design support ducts and provide a lateral stability. There are 4 different models to suit hanging loads from 270Kg to 3400Kg.

All the **SFC Marine Exhaust mounts** are equipped with interlocking metal parts to withstand to high compression and traction loads. This failsafe feature provides an extra safety for the application. They also incorporate a thermal insulation plate to prevent the compound to be exposed to high temperatures that may put in risk the thermostability of the elastic compound.

Advantages

Easy Installation

This mount requires minimal structural modifications, making installation quick and straightforward.

Mount offering high stability

Suspensions built with this mount barely move, thanks to a geometry designed to control the movement of the suspended element.

High robustness in dynamic applications for improved durability

These mounts offer enhanced robustness and are designed to withstand extreme load peaks. They are especially recommended where good durability is required in demanding applications.

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalogue without prior notice.
Document generated on 07/11/2026.