Threaded Insert for Square Tube

Reinforced polyamide threaded insert for square tubing, designed for fitting levelling feet without welding.



The **AMC-MECANOCAUCHO® Threaded Inserts for Square Tubes** provide a simple way of incorporating a **threaded fixing point into square tubular profiles**, particularly for the installation of levelling feet.

Manufactured from **reinforced polyamide**, they are designed to be **press-fitted directly into the end of the tube**, providing quick and simple installation without welding.

The **metal threaded insert** provides a robust connection for the levelling foot and facilitates adjustment or replacement when required.


This design provides a practical and cost-effective option for **machine frames, conveyors, tubular structures and industrial equipment** manufactured from square tubing.

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalogue without prior notice.
Document generated on 15/11/2026.

Drawings

SQUARE TUBE



Type	Code	Max. Load(kg)	H(mm)	L(mm)	M	Weight(kg)	Tube Thickness	D1(mm)	D2(mm)
SQUARE TUBE	159551	500	6	31	M10	0.029	3,55	30	27
	159552	550	6	31	M12	0.027	3,55	30	27
	159553	700	8	38	M10	0.035	3,8	35	32
	159554	750	8	38	M12	0.033	3,8	35	32
	159555	850	8	38	M16	0.037	3,8	35	32
	159556	750	8	38	M10	0.051	4	40	37
	159557	800	8	38	M12	0.048	4	40	37
	159558	850	8	38	M14	0.05	4	40	37
	159559	900	8	38	M16	0.049	4	40	37
	159560	750	8	38	M10	0.042	4	40	36
	159561	800	8	38	M12	0.079	4	40	36
	159562	850	8	38	M14	0.05	4	40	36
	159563	900	8	38	M16	0.044	4	40	36
	159564	950	8	38	M20	0.059	4	40	36
	159565	800	10	45	M12	0.079	4	50	47
	159566	850	10	45	M14	0.081	4	50	47
	159567	900	10	45	M16	0.076	4	50	47
	159568	950	10	45	M20	0.091	4	50	47
	159569	800	10	45	M12	0.07	4	50	45
	159570	850	10	45	M14	0.081	4	50	45
	159571	900	10	45	M16	0.076	4	50	45
	159572	950	10	45	M20	0.086	4	50	45

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalogue without prior notice.
Document generated on 15/11/2026.

Advantages

Easy Installation

This mount requires minimal structural modifications, making installation quick and straightforward.

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalogue without prior notice.
Document generated on 15/11/2026.