

SVT Anti-Vibration Mounts

Stainless steel wire mesh anti-vibration mounts for vibration and shock isolation at high temperatures and in severe environments.



The **SVT anti-vibration mounts from AMC-MECANOCAUCHO®** use a resilient **stainless steel wire mesh element**, specifically designed to provide effective **vibration isolation in high-temperature applications** and in environments where conventional elastomers are not suitable.





Their design provides **similar stiffness in compression and tension**, making them particularly suitable for equipment subjected to **vertical vibration, shocks and high dynamic loads**. The wire mesh also provides a **high level of damping**, helping to limit vibration amplification when passing through resonance.

The robust metal housing withstands **tensile loads**, while the stainless steel wire mesh provides excellent resistance to **corrosion, high temperatures and severe environmental conditions**.

SVT mounts are particularly suitable for **ships, railway vehicles, transport equipment and mobile machinery**, as well as **engines, pumps, auxiliary units and exhaust systems** exposed to high temperatures and severe dynamic loads.

Drawings

SVT-70 / SVT-95



Type	Max.Load (kg)	Weight(gr)	Code
SVT-70	300	1581	176650
SVT-95	1400	2900	176670

Technical characteristics

SVT mounts are anti vibration mounts that use a pre-stressed stainless steel mesh as elastic element. They are ideal for applications in which high temperatures are present. Its specific design allows very similar tensile and compression stiffness rates. This feature is particularly useful on those applications where vibration in the vertical sense is predominant. The metal parts are robust and incorporate a fail-safe device in order to resist tensile loads.

The steel housing has been designed to withstand to great dynamic shocks while the stainless steel mesh fits tight to avoid relative displacements.

The stainless steel wire mesh and the PU coated carbon steel housing provide a higher resistance to corrosive environments.

Moreover, the damping properties of the stainless steel wire mesh allows low amplification on resonance, allowing stable suspended elements.