MPR+Sylomer®

Resilient Sylomer® mounts for fitness equipment and weight training areas. Reduce vibration and impact noise transmission, particularly from dropped weights.



The **MPR + Sylomer® AMC-MECANOCAUCHO®** resilient mounts are specifically designed to **reduce the transmission of vibration, impact noise, and structure-borne sound** generated by fitness equipment and weight training activities.

Installed beneath machines, platforms, or weightlifting areas, they use the resilient properties of **Sylomer® to absorb the energy generated by impacts and dropped weights**, thereby reducing its transmission into the floor and building structure.

Different Sylomer® grades allow the mounts to be matched to the **load and required level of isolation**, optimizing their performance for each application.

MPR + Sylomer® mounts are particularly suitable for **gyms, weight rooms, weightlifting areas, and fitness facilities** where controlling vibration, impact noise, and structure-borne sound is essential.

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain

Tel.: +34 843 74 00 13
Fax: +34 943 69 62 19

sales@amcsa.es

www.mecanocaucho.com
www.akustik.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalog without prior notice.

Drawings

MPR 110



Type	Code	Max. Load(lbs)	Color	Thickness(in)
MPR 110	712386	66	Brown	0.47
	712321	66	Brown	0.98

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain

Tel.: +34 843 74 00 13
Fax: +34 943 69 62 19

sales@amcsa.es

www.mecanocaucho.com
www.akustik.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalog without prior notice.

MPR 220



Type	Code	Max. Load(lbs)	Color	Thickness(in)
MPR 220	712387	110	RED	0.47
	712322	110	RED	0.98

MPR 450



Type	Code	Max. Load(lbs)	Color	Thickness(in)
MPR 450	712388	220	GREY	0.47
	712323	220	GREY	0.98

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain

Tel.: +34 843 74 00 13
Fax: +34 943 69 62 19

sales@amcsa.es

www.mecanocaucho.com
www.akustik.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalog without prior notice.

Elastic properties









AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain

Tel.: +34 843 74 00 13
Fax: +34 943 69 62 19

sales@amcsa.es

www.mecanocaucho.com
www.akustik.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalog without prior notice.

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain

Tel.: +34 843 74 00 13
Fax: +34 943 69 62 19

sales@amcsa.es

www.mecanocaucho.com
www.akustik.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalog without prior notice.