

TFS Washer

Zinc-plated steel safety washer for TFS mounts, designed to provide mechanical retention and maintain the fail-safe configuration under high dynamic loads.



The **AMC-MECANOCAUCHO® TFS washer** is specifically designed to complete the installation of **TFS mounts** and provide secure **mechanical retention of the equipment**.

Combined with the elastomer elements of the TFS mount, it creates a **fail-safe configuration**, limiting excessive movement in tension and compression under shocks, overloads or high dynamic loads.

Its geometry allows the elastomer to deform as required for effective **vibration isolation**, while providing a **mechanical safety stop** when movement reaches the designed limits.

Manufactured from **zinc-plated steel**, the washer provides high corrosion resistance and excellent durability for mobile and industrial applications operating under demanding conditions.



AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain



Tel.: +34 843 74 00 13



sales@amcsa.es



www.mecanocaucho.com

Drawings

TFS 25

Type	Weight(gr)	Ø ext.(mm)	Ø int.(mm)	Thickness(mm)	Code
TFS 25	10	28,2	10,5	2	606185



AMC MECANOCAUCHO
 Industrialdea Zona A - Pab. 35.
 Asteasu E-20159, Gipuzkoa
 Spain



Tel.: +34 843 74 00 13



sales@amcsa.es



www.mecanocaucho.com

Technical characteristics

Washers should be used, if the rubber surface is not covered with the contact surface. Washers upon request.