

4V-SH Spring Mount

Open high-deflection spring mount for very low-frequency vibration isolation. Static deflection up to 50 mm (2 inches) and natural frequencies as low as 3 Hz.



The **AMC-MECANOCAUCHO® 4V-SH spring mount** is designed for applications requiring **very low-frequency vibration isolation** and high load capacity.


With a **static deflection of up to 50 mm (2 inches)**, the springs can achieve **natural frequencies as low as 3 Hz**, providing highly effective isolation for low-speed equipment or machinery generating very low-frequency vibrations.

Its open design provides **no lateral restraint**, so particular attention must be paid to **equipment stability and the position of its centre of gravity**.

The spring mount incorporates a **levelling system** and a **Sylomer® pad**, complementing the action of the springs by improving vibration isolation at medium and high frequencies.

Drawings


4V-SH



Type	Code	Spring color	Max. Load (kg)	K(N/mm)	A(mm)	B(mm)	C(mm)	D(mm)	E(mm)	F(mm)	G(mm)	H(mm)	I(mm)	Weight(kg)
4V-SH	21030	BLUE	268	54	250	180	M20	200	14	210	260	288	206	11.15
	21031	WHITE	380	74	250	180	M20	200	14	210	260	288	206	11.95
	21032	BLACK	492	100	250	180	M20	200	14	210	260	288	206	12.2
	21033	BEIGE	692	138	250	180	M20	200	14	210	260	288	206	12.49
	21034	RED	892	172	250	180	M20	200	14	210	260	288	206	12.72
	21035	GREY	1340	274	250	180	M20	200	14	210	260	288	206	13.14
	21036	GREEN	1784	351	250	180	M20	200	14	210	260	288	206	13.727
	21039	BROWN	2800	601	250	180	M20	200	14	210	260	288	206	13.727

Elastic properties

LOAD DEFLECTION GRAPH
AMC MECANOCAUCHO® 4V-SH



Technical characteristics

The mounts are able to reach low natural frequencies from 2 to 5 Hz. The spring combined with sylomer® is able to provide high isolation at low and medium frequencies.

The curves are showing the deflection and natural frequencies according to the load of the spring. Temperature working range from -30 to 70°. Short term higher temperatures are possible.