

6V-SR Spring Mount

High-capacity spring mount with Sylomer® base, offering up to 30 mm (1.2 in) static deflection and a natural frequency as low as 4 Hz.



The **AMC-MECANOCAUCHO® 6V-SR Spring Mount** is designed for the **vibration isolation of machinery and equipment with high loads**, requiring a low natural frequency and effective low-frequency vibration isolation.


With a **static deflection of up to 30 mm (1.2 in)**, the springs provide **natural frequencies as low as 4 Hz**, ensuring effective low-frequency vibration isolation.

An **integrated levelling system** facilitates height adjustment and accurate levelling of the equipment during installation.

The 6V-SR Spring Mount is supplied as standard with a **Sylomer® base**, which complements the action of the springs by reducing the transmission of **mid and high frequencies that may propagate through the steel springs**. The **springs + Sylomer® combination** therefore provides effective vibration isolation over a broader frequency range.


Drawings

6V-SR



Type	Code	Max. Load (kg)	Spring color	K(N/mm)	A(mm)	B(mm)	D(mm)	E(mm)	F(mm)	G(mm)	H(mm)	I(mm)	Weight(kg)
6V-SR	21330	1200	BLACK	384	350	180	200	18	300	360	396	206	18,443
	21331	2400	BLACK	802	350	180	200	18	300	360	396	206	18,443
	21101	3900	BLACK	1086	350	180	200	18	300	360	396	206	19,75
	21102	4800	BLACK	1724	350	180	200	18	300	360	396	206	19,9
	21103	6000	BLACK	2107	350	180	200	18	300	360	396	206	21,73
	21104	7200	BLACK	3020	350	180	200	18	300	360	396	206	22,174

Elastic properties



Technical characteristics

The mounts are able to reach low natural frequencies from 3 to 5 Hz. The spring combined with sylomer® is able to provide high isolation at low and medium frequencies.

The curves are showing the deflection and natural frequencies according to the load of the spring. Temperature working range from -30 to 70°. Short term higher temperatures are possible.