

6V-SR Spring Isolator

High-capacity spring isolator with Sylomer® base, offering up to 1.2 in (30 mm) static deflection and a natural frequency as low as 4 Hz.



The **AMC-MECANOCAUCHO® 6V-SR Spring Isolator** is designed for the **vibration isolation of machinery and equipment with high loads**, requiring a low natural frequency and effective low-frequency vibration isolation.


With a **static deflection of up to 1.2 in (30 mm)**, the springs provide **natural frequencies as low as 4 Hz**, ensuring effective low-frequency vibration isolation.

An **integrated leveling system** facilitates height adjustment and accurate leveling of the equipment during installation.

The 6V-SR Spring Isolator is supplied as standard with a **Sylomer® base**, which complements the action of the springs by reducing the transmission of **mid and high frequencies that may propagate through the steel springs**. The **springs + Sylomer® combination** therefore provides effective vibration isolation over a broader frequency range.


Drawings

6V-SR



Type	Code	Max. Load (lbs)	Spring color	K(N/mm)	A(in)	B(in)	D(in)	E(in)	F(in)	G(in)	H(in)	I(in)	Weight(lbs)
6V-SR	21330	2645	BLACK	384	13.78	7.09	7.87	0.71	11.81	14.17	15.59	8.11	41
	21331	5290	BLACK	802	13.78	7.09	7.87	0.71	11.81	14.17	15.59	8.11	41
	21101	8596	BLACK	1086	13.78	7.09	7.87	0.71	11.81	14.17	15.59	8.11	44
	21102	10579	BLACK	1724	13.78	7.09	7.87	0.71	11.81	14.17	15.59	8.11	44
	21103	13224	BLACK	2107	13.78	7.09	7.87	0.71	11.81	14.17	15.59	8.11	48
	21104	15869	BLACK	3020	13.78	7.09	7.87	0.71	11.81	14.17	15.59	8.11	49

Elastic properties



Technical characteristics

The mounts are able to reach low natural frequencies from 3 to 5 Hz. The spring combined with sylomer® is able to provide high isolation at low and medium frequencies.

The curves are showing the deflection and natural frequencies according to the load of the spring. Temperature working range from -30 to 70°. Short term higher temperatures are possible.