VT-HD



AMC-MECANOCAUCHO® VT HD Hangers range is a range designed for suspension of acoustic ceilings and machinery that requires a very high isolation level.

These hangers are made of a high mechanical performance spring and incorporate a rubber bush conceived to avoid the acoustic bridges and the contact of a non aligned screw.

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain

Tel.: +34 843 74 00 13


sales@amcsa.es

www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalog without prior notice.
Document generated on 16/11/2026.

Drawings

VT-67 HD / VT-95 HD / VT-123 HD / VT-173 HD / VT-223 HD / VT-335 HD / VT-446 HD / VT-700 HD




Type	Max. Permanent Load (lbs)	Spring color	Deflection(in)	Code
VT-67 HD	148	BLUE	1.97	20235
VT-95 HD	209	WHITE	1.97	20239
VT-123 HD	271	BLACK	1.97	20236
VT-173 HD	381	BEIGE	1.97	20240
VT-223 HD	491	RED	1.97	20237
VT-335 HD	738	GREY	1.97	20241
VT-446 HD	983	GREEN	1.97	20238
VT-700 HD	1543	BROWN	1.97	20243

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalog without prior notice.
Document generated on 16/11/2026.

Elastic properties



AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalog without prior notice.
Document generated on 16/11/2026.

Technical characteristics

The metallic structure is very robust and it is supplied with an anti-corrosive zinc-plated coat.

The assembly of this hanger is very simple, as it can be directly fastened to the ceiling through its top hole and a stud bolt can be directly fastened to the nut placed over the spring.

AMC-MECANOCAUCHO® VT HD Hangers, due to their low stiffness, are able to reach natural frequencies from 2 to 5Hz, and are specially suitable for applications where high isolation level is required.
<Moreover, these hangers assure the stability of the suspended equipment by limiting the deflection that can be achieved.

NEVER METAL TO METAL CONTACT

The hanger has a clearance that allows the threaded rod to swing within a 35° angle envelope to absorb irregularities in the ceiling.

AMC MECANOCAUCHO
Industrialdea Zona A - Pab. 35.
Asteasu E-20159, Gipuzkoa
Spain
Tel.: +34 843 74 00 13
sales@amcsa.es
www.mecanocaucho.com

In order to adapt its products to the state of the art, Aplicaciones Mecánicas del Caucho, S.A. reserves the right to modify the conception and manufacture of the materials presented in this catalog without prior notice.
Document generated on 16/11/2026.